

POWER


Ningbo Power (Joro)
Sanitary Electrical Appliance Co Ltd






Tel:0086-574-87664043, 0574-27892829 Fax: 0574-27892829, 0086-574-87665949

Email:sales@sino-handdryer.com Website:<http://www.sino-handdryer.com>



Msn:Jbx110@hotmail.com Skype:Jbx110 Contact Person:Mr. Jerry Jiang

PHOTO OF PRODUCT	FEMALE THREAD SAVING TYPE
	Type: PW-175S
	Weight: 0.015 kg
	Water saving: 84%
	Color: silver
	Material: bronze, chrome plating, plastic (pom)
	Applicable hydraulic pressure range: 1-5kgf/cm2
	Scope of application: M24x1, female
Installment Instructions 1 Cut off the water supply. 2 Unscrew A and B for one and a half thread and keep them unlocked. 3 Insert the combination of A and B into the faucet's water outlet till the two-piece component perfectly matches the outlet. 4 Screw up three hex socket cap screws in part B respectively with a hexagonal wrench. 5 Use flexible wrench to assist in screwing up part A and part B. 6 Reinststate the water supply (the faucet shall be unlocked). 7 The installation of touch-sensitive faucet is accomplished.	

DIY It explains to install

1 Shut off the water supply.  Remove existing aerator and set off screw using a wrench.	2 Tighten  Attach "One Touch" tap's nozzle, fasten it up using a wrench.	3 Turn on  Now turn on the water (leave the tap in the on position)
---	--	--

Operation instructions

1  Press once for water output and the second press for water off	2  Temperature controlled by faucet's switch. Keep in cold water position after using hot water.	Precautions <ul style="list-style-type: none">◆ Turn off faucet if water non-supplied◆ Turn off hot water and turn back to cold water after using hot water to avoid hot water's flowing back to effect water boiler's function
---	--	---

Address : No.618 Zhenming Road, Chuangye Yuan Free Zone Ningbo Zhejiang China

